

Wear Protection Sleeve Secutex

Product information



General: Special wear protection for roundslings and webbing slings, intended for lift of load with cutting edges. Extremely good cutting resistance and high wear strength.

Design: Single- or double side polyuretan coated polyester tube or double side polyurethane coated clip.

Max working temp: apx -30° - +70°C, short expose to apx +90°C.

[... Read more](#)

Material: Polyester with 5 mm polyurethane coating. Resistant to most acids but not strong alkalizes.

Wear Protection Sleeve Secutex

Technical data

| Part code | Code | Width mm | Height mm | Fit Webwidth mm | Fit Roundsling ton | Weight kg/m |
|------------|---------|----------|-----------|-----------------|--------------------|-------------|
| 8025SF1050 | SF1-50 | 70 | 23 | 50 | 1 | 0.9 |
| 8025SF1065 | SF1-65 | 80 | 23 | 60 | 2 | 1.1 |
| 8025SF1075 | SF1-75 | 95 | 25 | 75 | 3 | 1.3 |
| 8025SF1100 | SF1-100 | 125 | 25 | 90 | 4 | 1.5 |
| 8025SF1125 | SF1-125 | 145 | 25 | 120 | 5-6 | 1.9 |
| 8025SF1150 | SF1-150 | 175 | 25 | 240 | 8 | 2.1 |
| 8025SF1300 | SF1-300 | 330 | 28 | 300 | ≥10 | 3.7 |

Protecting sleeves SF-2/double side

| Art No | Code | Fit Web width mm | Round sling tons | Width mm | Height mm | Weight kg/m |
|--------------|----------|------------------|------------------|----------|-----------|-------------|
| 05.30SF2.050 | SF-2.50 | 50 | 1 | 70 | 25 | 1,2 |
| 05.30SF2.065 | SF-2.65 | 60 | 2 | 80 | 25 | 1,5 |
| 12.40SF2.075 | SF-2.75 | 75 | 3 | 95 | 25 | 1,8 |
| 05.30SF2.100 | SF-2.100 | 90 | 4 | 125 | 25 | 2,1 |
| 05.30SF2.125 | SF-2.125 | 120 | 5-6 | 145 | 25 | 2,6 |
| 12.40SF2.150 | SF-2.150 | 240 | 8 | 175 | 25 | 3,0 |
| 12.40SF2.300 | SF-2.300 | 300 | ≥10 | 330 | 30 | 6,5 |

Clamp sleeves SC/double side

Wear Protection Sleeve Secutex

| | Code | Fit | | Width | Height | Weight |
|-------------|--------|-----------|-------------|-------|--------|--------|
| | | Web width | Round sling | | | |
| Art No | | mm | tons | mm | mm | kg/m |
| 12.40SC.050 | SC.50 | 50 | 1 | 70 | 25 | 1,1 |
| 05.30SC.065 | SC.65 | 65 | 2 | 80 | 25 | 1,3 |
| 05.30SC.075 | SC.75 | 75 | 3 | 95 | 25 | 1,6 |
| 05.30SC.100 | SC.100 | 100 | 4 | 125 | 25 | 1,8 |
| 05.30SC.125 | SC.125 | 125 | 5 | 145 | 25 | 2,3 |
| 12.40SC.150 | SC.150 | 150 | 8 | 175 | 25 | 2,6 |
| 12.40SC.300 | SC.300 | 300 | ≥10 | 330 | 30 | 6,3 |