

Push Trolley type 20

Product information

Low-built block trolley for hanging e.g. chain blocks and wire hoists. The trolley can be supplied with a load of 0.5 tons up to 5 tons. The trolley has corner protection which prevents the trolley from detaching from the beam and ball bearing wheels. It is easily adjustable by the left- and right-handed carrier bracket and fits most brands of hoists.

Marking: WLL, name plate and CE.
Finish: Black painted.

Part Code	WLL ton	Beam width mm mm	Type	Min curve r m	A min-max	B mm	C mm	Ø D mm	E mm	F mm	G mm	H mm	Ø J mm	Ø K mm	L mm	M mm	P mm	Weight kg	Delivery time
502300051600420	0.5	46-160	20123A	1,0	46-160	208	18	62	77	18	45	33	25	19	216	100	24	6	20
502300052800420	0.5	161-280	20124A	1	161-280	208	18	62	77	18	45	33	25	19	216	100	24	6.4	20
502300101610420	1	50-161	20143A	1,25	50-160	212	20	70	85	20	51	40	32	24	264	130	26	9.4	20
502300102800420	1	161-280	20144A	1,25	161-280	212	20	70	85	20	51	40	32	24	264	130	26	10.7	20
502300201800420	2	64-180	20163A	1,80	64-180	248	24	100	118	25	63	51	40	32	345	165	30	19	20
502300203000420	2	181-300	20164A	1,80	181-300	248	24	100	118	25	63	51	40	32	345	165	30	21	20
502300301800420	3	74-180	20173A	2,20	74-180	262	28	114	137	31	78	57	46	35	384	180	35	31.5	20
502300303000420	3	181-300	20174A	2,20	181-300	262	28	114	137	31	78	57	46	35	384	180	35	34	20
502300501800420	5	82-180	20193A	2,50	82-180	270	34	140	165	34	92	64	56	42	455	215	40	55	20
502300503000420	5	181-300	20194A	2,50	181-300	270	34	140	165	34	92	64	56	42	455	215	40	58	20

Blueprint

