

Electric Chain Hoist NOVA Blackline

Product information



General: The NOVA Blackline meets the high demands of a SWF hoist in regards to safety, quality and reliability.

- Ultimate load from 2-12,5 tons and a lifting weight up to 12 meters
- Optimal space and land utilization due to compact headroom and optimum hook dimension
- Minimized attrition of rope by a big drum diameter
- Robust contactor control for hoist motor and trolley motor
- Mechanical overload protection protects crane and building structure
- Plug and play - quick and easy installation and maintenance
- Overheat protection

Part code	Code	Lifting height m	Max load kg	FEM	Lifting speed m/min.	ISO	Trolley speed m/min	Delivery time
6041	NOVA BB	6	2,000	2m	5/0,8	M5	20/5	20
6041	NOVA BB	9.5	2,000	2m	5/0,8	M5	20/5	20
6041	NOVA BB	6	2,500	3m	5/0,8	M6	20/5	20
6041	NOVA BB	9.5	2,500	3m	5/0,8	M6	20/5	20
6041	NOVA BB	6	3,200	2m	5/0,8	M5	20/5	20
6041	NOVA BB	9.5	3,200	2m	5/0,8	M5	20/5	20
6041	NOVA BC	6	4,000	3m	5/0,8	M6	20/5	20
6041	NOVA BC	9	4,000	3m	5/0,8	M6	20/5	20
6041	NOVA BC	6	5,000	2m	5/0,8	M5	20/5	20
6041	NOVA BC	9	5,000	2m	5/0,8	M5	20/5	20
6041	NOVA BC	6	6,300	1Am	4/0,7	M4	20/5	20
6041	NOVA BC	9	6,300	1Am	4/0,7	M4	20/5	20
6041	NOVA BD	9	8,000	3m	5/0,8	M6	20/5	20
6041	NOVA BD	12	8,000	3m	5/0,8	M6	20/5	20
6041	NOVA BD	9	10,000	2m	5/0,8	M5	20/5	20
6041	NOVA BD	12	10,000	2m	5/0,8	M5	20/5	20
6041	NOVA BD	9	12,500	1Am	4/0,7	M4	24/6	20
6041	NOVA BD	12	12,500	1Am	4/0,7	M4	24/6	20