

Horizontal Lifting Clamp TDH



Product information

Lightweight heavy duty clamp for safe and easy lifting of sheets that will bend or deflect when being lifted.
Jaw openings available from: 0 to 50 mm

Features:

- Compact design and high lifting capacity
- Lightweight design for easy handling
- Tough quality heavy duty welded body

Marking: According to standard, CE-marked, Type, serial number, WLL, Jaw opening.

Temperature range: - 40°C to +100°C

Standard: EN 13155

Note: Must always be used in pairs (or multiple pairs)

Warning: Hardness level of the material surface may not exceed 37 Hrc (345 Hb, 1166 N/mm²)

| Part code | Code | WLL ton | Jaw width mm | H mm | S mm | T mm | U mm | V mm | W mm | X mm | Y mm | Weight kg | Delivery time |
|-----------------|-------|---------|--------------|------|------|------|------|------|------|------|------|-----------|---------------|
| 502100100150690 | 1 TDH | 1 | 0-15 | 13.5 | 99 | 22.5 | 167 | 140 | 10 | 65 | 15 | 2.5 | 7 |
| 502100200350690 | 2 TDH | 2 | 0-35 | 14 | 114 | 26 | 233 | 180 | 20 | 80 | 15 | 8 | 7 |
| 502100400500690 | 4 TDH | 4 | 0-50 | 25 | 129 | 40 | 304 | 235 | 30 | 130 | 20 | 18 | 7 |
| 502100600500690 | 6 TDH | 6 | 0-50 | 25 | 129 | 40 | 304 | 235 | 30 | 130 | 20 | 18 | 7 |

Blueprint

