Lifting Solutions Group
Axel Johnson International

Swivel Point 8-271

Product information



- Swings more than 180°, rotates through 360° due to its unique ball bearing design. Secured four times against breakage in all load directions.
- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts and cap screw are traceable to Test Certification.
- Proof tested to 2.5 times the WLL.
- Fatigue rated to 1.5 times the WLL.
- Easy to measure disposal stage by using with the new WLL tables.
- Easy to attach or dismantle due to the forged hexagon shaped body of the Super Point.
- Maximum WLL in axial direction when load ring is aligned.
- Capable of rotating under load. Do not turn continuously in 90 degree direction at full load.

... *Read more*

Material: Forged alloy steel, quenched and tempered.
Marking: According to standard, CE-mark
Finish: Painted.
Standard: EN 1677-1
Note: Capable of rotating under load. Do not turn continuously in 90 degree direction att full load.

Safety factor: 4:1


Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Swivel Point 8-271

Blueprint



Technical data

Part code	WLL ton	Thread mm	Pitch DIN13	Torque Nm	G mm	C mm	K mm	H mm	F mm	D mm	B mm	A mm	E mm	M mm	Weight kg
42158271004	0.6	M 10	1,5	10	35	40	30	16	72	8	32	29	15	M 10	0.2
42158271020	2.5	M 20	2,5	70	62	68	55	29	122	13	54	36	30	M 20	1
42158271035	4	M 24	3	150	78	88	70	36	154	19	66	41	36	M 24	2.2

Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved