



Clevis Foundry Hook X-046 Grade 10

Product information

At least 25% greater WLL than traditional Grade 8 products.

Testing according to DIN PAS 1061 and ASTM A952/A 952M.

Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.

Tempering temperature minimum 400°C.

Designed for the assembly of chain slings where wide throat openings are necessary.

Material: Quenched and tempered alloy steel.

Marking: According to standard, Size, grade, manufacturer ID, traceability.

Temperature range: -40°C up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-1

Warning: Before using the hook, check whether hooks without safety latches are allowed to be used for the particular application.

Safety factor: 4:1

Grade: 10

Part Code	WLL ton	For chain Grade 10 Ø mm	A mm	H mm	K mm	P mm	T mm	Weight kg	Delivery time
402300250770	2.5	7,8	9	27	133	62	19	0.95	2
402300400770	4	10	11	32	163	74	23	1.8	2
402300670770	6.7	13	14	39	200	88	32	3.6	20
402301000770	10	16	18	47	239	98	41	6.4	20
402301600770	16	20	21	62	305	113	46	11.2	20

Blueprint

