

Lifting Solutions Group
Axel Johnson International

Elevator rope 8x19S-FC

Product information



Elevator



General: Steel wire rope for use in elevator.

Tolerance:≤10 mm 0% − +6%, 10 mm 0% − +5%.

... *Read more*

Rope construction: 8x19S-FC, Seal.
Marking: According to standard
Finish: Ungalvanised.
Standard: EN 12385-5

Fill factor: 0.44

Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Elevator rope 8x19S-FC

Technical data

Part code	Rope diameter mm	Tensile strength N/mm²	Finish	Rope lay	Min. breaking force kN	Steel area mm²	Lubrication	Weight kg/100m
106100804130209	8	1,370/1,770	Bright	sZ	28.1	22	SupplierStandard	22.2
106101004130209	10	1,370/1,770	Bright	sZ	44	34.9	SupplierStandard	34
106101104130209	11	1,370/1,770	Bright	sZ	53.2	42.2	SupplierStandard	41
106101204130209	12	1,370/1,770	Bright	sZ	63.3	50.3	SupplierStandard	49

Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved