

Elevator rope 8x19S-FC

Product information



General: Steel wire rope for use in elevator.

Tolerance: ≤10 mm 0% - +6%, 10 mm 0% - +5%.

Rope construction: 8x19S-FC, Seal.


Marking: According to standard

Finish: Ungalvanised.

Standard: EN 12385-5

Fill factor: 0.44

Elevator



| Part code | Rope diameter mm | Tensile strength N/mm ² | Finish | Rope lay | Min. breaking force kN | Steel area mm ² | Lubrication | Weight kg/100m | Delivery time |
|-----------------|---------------------|---------------------------------------|--------|----------|---------------------------|-------------------------------|------------------|-------------------|---------------|
| 106100804130209 | 8 | 1,370/1,770 | Bright | sZ | 28.1 | 22 | SupplierStandard | 22.2 | 2 |
| 106101004130209 | 10 | 1,370/1,770 | Bright | sZ | 44 | 34.9 | SupplierStandard | 34 | 2 |
| 106101104130209 | 11 | 1,370/1,770 | Bright | sZ | 53.2 | 42.2 | SupplierStandard | 41 | 2 |
| 106101204130209 | 12 | 1,370/1,770 | Bright | sZ | 63.3 | 50.3 | SupplierStandard | 49 | 2 |