

## Elevator rope 8x19S-IWRC

### Product information



**General:** Steel wire rope for use in elevator.

**Tolerance  $\varnothing$ :**  $\leq 10$  mm 0% - +6%,  $> 10$  mm 0% - +5%.

**Rope construction:** 8x19-IWRC.


**Marking:** According to standard

**Finish:** Ungalvanised

**Standard:** EN 12385-5

**Fill factor:** 0.59

Elevator



Part code	Rope diameter mm	Tensile strength N/mm <sup>2</sup>	Finish	Rope lay	Min. breaking force kN	Steel area mm <sup>2</sup>	Lubrication	Weight kg/100m	Delivery time
106100804020219	8	1,570	Bright	sZ	37.9	31.1	SupplierStandard	27	20
106100904020219	9	1,570	Bright	sZ	48	38.1	SupplierStandard	34	20
106101004020219	10	1,570	Bright	sZ	58.5	46.6	SupplierStandard	41	20
106101104020219	11	1,570	Bright	sZ	69.7	55.6	SupplierStandard	49	20
106101204020219	12	1,570	Bright	sZ	83.6	66.4	SupplierStandard	59	20
106101304020219	13	1,570	Bright	sZ	100	79.5	SupplierStandard	70	20
106101404020219	14	1,570	Bright	sZ	116	91.8	SupplierStandard	81	20
106101504020219	15	1,570	Bright	sZ	131	104	SupplierStandard	92	20
106101604020219	16	1,570	Bright	sZ	148	118	SupplierStandard	105	20