

Concrete pipe clamp slings

Product information



Six different concrete pipe clamps slings with 2- and 3-legs. P model slings are equipped with a standard jaw. In the I model slings, the jaw is wider than normal, and in the K model slings, the jaw is higher than normal and is suitable for concrete pipes equipped with rubber rings. In all models, the chain length is 1.5 m.

Models:

- **KRT2P:** 2-legs | chain leg 1,5 m | standard jaw P-model
- **KRT2I:** 2-legs | chain leg 1,5 m | wide jaw I-model
- **KRT2K:** 2-legs | chain leg 1,5 m | high jaw K-model | with a rubber sealing pipe clamps
- **KRT3P:** 3-legs | chain leg 1,5 m | standard jaw P-model
- **KRT3I:** 3-legs | chain leg 1,5 m | wide jaw I-model
- **KRT3K:** 3-legs | chain leg 1,5 m | high jaw K-model | with a rubber sealing pipe clamps

[You can also order the jaws individually – you can find them here.](#)

... [Read more](#)

Material: Steel

Marking: CE-marked

Finish: Painted, yellow

Note: L-dimension is height of jaw's grip area

Warning: Not to be heat-treated

Safety factor: 4:1

Concrete pipe clamp slings

Blueprint



Technical data

Part code	Code	WLL ton	Jaw width mm	L mm	Weight kg
502100201201200	KRT2P	2	60-120	245	25
502100301201200	KRT3P	3	60-120	245	37