



PAWO F3

Product information



Special rope with steel-reinforced fiber core for elevators.

PAWO F3 has a proven history in many types of traction elevator applications. The outer strands are designed in Seale construction. The 9 thicker wires of the outer strand layer offer a higher wear resistance.

The rope is primarily used where the service life is more defined by wear due to contact with the traction sheave than by rope fatigue due to bending. Deformations of the rope cross-section can be greatly reduced. The fiber content in the core of the steel wire rope works as a lubricant reservoir.

Properties

- Low and mid-rise
- small to intermediate number of bending cycles
- normal to heavy usage levels
- wear-resistant
- low elongation
- extended service life

Rope construction: 8x19 Seale with steel-reinforced core.

Marking: According to standard

Standard: EN 12385-5

Part code	Rope diameter mm	Tensile strength N/mm ²	Finish	Rope lay	Min. breaking force kN	Steel area mm ²	Lubrication	Weight kg/m	Delivery time
106100654020149	6.5	1,570	Bright	sZ	25.9	-	SupplierStandard	0.16	2
106100804020149	8	1,570	Bright	sZ	38	-	SupplierStandard	0.24	20
106101004020149	10	1,570	Bright	sZ	60.5	-	SupplierStandard	0.39	20
106101104020149	11	1,570	Bright	sZ	73.4	-	SupplierStandard	0.47	20
106101304020149	13	1,570	Bright	sZ	103.1	-	SupplierStandard	0.66	20