

Weld-on Lifting Ring RUD VLBS-U with spring

Product information



- Suspension ring pivots 180°
- Suspension ring & weld-on-block of the VLBS-U are undetachable
- Suspension ring can be angled into position (VLBS-U)

Clamping spring works as a noise reduction and holds the suspension ring in the requested position; therefore simple hinge of lashing mean possible.


... [Read more](#)

Marking: According to standard
Temperature range: -40° up to +200°C
Standard: EN 1677-1

Safety factor: 4:1

Weld-on Lifting Ring RUD VLBS-U with spring

Blueprint



Technical data

| Part code | Code | WLL ton | A mm | B mm | C mm | D mm | E mm | F mm | G, mm | H, mm | T mm | Weight kg |
|-------------|-------------------------|---------|------|------|------|------|------|------|-------|-------|------|-----------|
| 42157994830 | VLBS-U-2,5t with spring | 2.5 | 38 | 77 | 28 | 45 | 47 | 16 | 40 | 16 | 75 | 0.53 |
| 42157993036 | VLBS-U-4t with spring | 4 | 42 | 87 | 31 | 51 | 52 | 18 | 46 | 16 | 83 | 0.72 |
| 42157993037 | VLBS-U-6,7t with spring | 6.7 | 61 | 115 | 44 | 67 | 73 | 24 | 60 | 22.5 | 117 | 1.89 |
| 42157993040 | VLBS-U-10t with spring | 10 | 75 | 129 | 55 | 67 | 71 | 26.5 | 60 | 26.5 | 126 | 2.76 |