

Master link assemblies 3-4-I, grade 80

Product information



Masterlink for 3- and 4-leg chain sling assemblies.

[... Read more](#)

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow

Standard: EN 1677-4


Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

Master link assemblies 3-4-I, grade 80

Blueprint



Technical data

Part code	WLL ton	EWL mm	For chain, 3-4-leg mm	L mm	B mm	D mm	B1 mm	D1 mm	L1 mm	Weight kg
4011NRLI6	2.36	189	6	135	75	18	25	14	54	1.2
4011NRLI78	4.25	230	7/8	160	90	22	34	16	70	2.2
4011NRLI10	6.7	265	10	180	100	26	40	18	85	3.4
4011NRLI13	11.2	315	13	200	110	32	50	22	115	6
4011NRLI16	17	400	16	260	140	36	65	26	140	10
4011NRLI20	26.5	500	20	350	190	51	70	32	150	23.3
4011NRLI22	32	520	22	350	190	51	75	36	170	25.9
4011NRLI26	45	570	26	400	200	57	80	40	170	35.2
4011NRLI32	67	817	32	460	250	72	190	49	357	67.6