Lifting Solutions Group
Axel Johnson International

Round Sling - Blackline

Product information



Typically used in connection with theaters, scenes etc. where the round sling preferably should not be visible.
Design: Load carrying yarn covered with “seamless” black protection sleeve.
Stretch with working load: 2-3%.
Length tolerance: Nominal length (EWL) ±2%.

... *Read more*

Material: Polyester. Resistant to most acids but not to strong alkalizes.
Marking: According to standard, CE-mark, Manufacture ID, WLL, length, date.
Temperature range: Approx. -40° up to +100°C.
Standard: EN 1492-2

Safety factor: 7:1


Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Round Sling - Blackline

Blueprint



Technical data

Part code	WLL ton	EWL m	Colour
340100100100240	1	1	Black
340100100200240	1	2	Black
340100100300240	1	3	Black
340100100050240	1	0.5	Black
340100100150240	1	1.5	Black
340100200100240	2	1	Black
340100200200240	2	2	Black
340100200300240	2	3	Black

Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved