

## Round Sling Extreema® XS

### Product information



The Extreema® XS sling is a compact high-strength round sling designed for lifting operations in confined or restricted spaces. It is used where traditional slings are too bulky or require larger hardware. Manufactured from HMPE, it combines high load capacity with a small diameter, enabling efficient and controlled lifting in tight environments.

WLL range: 3 – 20t

EWL range: 0,5m – 16m, (15t/20t can be made up to 65m)

#### When to choose this product

##### Best for:

- Lifting in confined spaces with limited clearance
- Applications requiring compatibility with standard shackles

##### Product benefits

- Compact diameter enables lifting in restricted or hard-to-reach areas
- D:d ratio 1:1 allows use with standard bow shackles
- HMPE construction provides high strength with low weight
- Lightweight design simplifies transport, handling, and storage
- Seamless sleeve supports durability and extended service life

... [Read more](#)

**Material:** HMPE

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to +70°C

**Standard:** EN 1492-2

*except material*

**Safety factor:** 7:1

## Round Sling Extreema® XS

### Technical data

Part code	WLL ton	EWL m	Colour
340500300050030	3	0.5	Yellow
340500300100030	3	1	Yellow
340500300150030	3	1.5	Yellow
340500300200030	3	2	Yellow
340500300250030	3	2.5	Yellow
340500300300030	3	3	Yellow
340500300400030	3	4	Yellow
340500300500030	3	5	Yellow
340500500050030	5	0.5	Red
340500500100030	5	1	Red
340500500150030	5	1.5	Red
340500500200030	5	2	Red
340500500250030	5	2.5	Red
340500500300030	5	3	Red
340500500400030	5	4	Red
340500500500030	5	5	Red
340501000150030	10	1.5	Orange
340501000200030	10	2	Orange
340501000300030	10	3	Orange
340501000400030	10	4	Orange
340501000500030	10	5	Orange