Lifting Solutions Group
Axel Johnson International

Master Link Assembly MA POWERTEX

Product information



The POWERTEX Master Link Assembly MA is a welded master link assembly used as the top ring in three- and four-leg chain sling assemblies. As part of the POWERTEX Grade 10 lifting chain component range, it provides a reliable connection point

Available for 6 mm up to 22 mm chain and from WLL 3t up to WLL 40t.
All models are welded.

Best used for

- Three-leg and four-leg Grade 10 chain sling assemblies.
- Industrial lifting and rigging applications requiring a welded master link assembly.

Product benefits

- Grade 10 design delivers 25% higher capacity than traditional Grade 8 components.
- Welded construction provides a durable and reliable lifting connection.
- Conforms to EN 1677 Parts 1, 2, 3, and 4 with 25% increased WLL.
- Forged components are crack detection tested, with samples proof load tested for quality assurance.
- Factory type tested and fatigue rated to 20,000 cycles at 1.5 × WLL.
- Batch number traceability and a POWERTEX 2.2 certificate support inspection and documentation.
- The components may also be used with a Grade 8 chain to EN 818-2. In such a case, the chain sling must be rated to Grade 8 in accordance with EN 818-4

... *Read more*

Marking: According to standard, POWERTEX + Model (MA-6-10) + traceability code.
Temperature range: -40 °C upp till +200 °C utan reduktion av WL
Finish: Powder painted in red
Standard: EN 1677-4 (+25% WLL) , AS 3776
Note: All models are welded

Safety factor: 4:1
Grade: 10

Building a complete chain sling?

In the configurator, choose the number of legs, chain grade, length and hooks. It picks compatible components for you and shows the sling's working load limit, so you don't have to match parts one by one.

Configure your sling


Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Master Link Assembly MA POWERTEX

Blueprint



Technical data

Part code	Code	WLL ton	EWL mm	For chain, 3-4-leg mm	A mm	B mm	D mm	a mm	b mm	d mm	H mm	S mm	Weight kg
402100300770	MA-6-10	3	189	6	135	75	18	54	25	14	28	7	1.3
402100530770	MA-8-10	5.3	230	8	160	90	22	70	34	16	28	8	2.2
402100840770	MA-10-10	8.4	265	10	180	100	27	85	40	18	28	11	3.6
402101400770	MA-13-10	14	315	13	200	110	33	115	50	22	43	13	6.4
402102120770	MA-16-10	21.2	400	16	260	140	36	140	65	28	55	17	10.6
402103360770	MA-20-10	33.6	530	20	350	190	50	180	90	32	-	-	23.7
402104000770	MA-22-10	40	530	22	350	190	50	180	100	36	-	-	26

Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved