Lifting Solutions Group
Axel Johnson International

Fall Arrest Block with Steel Cable POWERTEX FBC

Product information



The robust FBC series fall arrest blocks are designed to provide maximum protection and security in the most demanding environments. It’s fitted with a top-quality steel wire rope, providing excellent protection if you fall over an edge. The solid black plastic housing and integrated shock absorber guarantee durability and reliability.

Equipped with a fall indicator that is integrated into the hooks swivel, and an integrated shock absorber, this block offers advanced safety features that meets the EN 360 standard.

The block is to be attached to an anchor point and the swivel hook to your safety harness. It is type-tested for vertical fall and against falling over an edge. It's available with a 6, 9, 12, or 18-meter long steel wire rope.

On top of the block, you'll find a swivel eye attachment point, and the block comes with a twist lock carabiner mounted to this swivel eye. A double-action aluminum hook with a rotating eye is connected to the wire rope on the bottom end. Finally, the block is RFID-equipped, completing the package.

Housing: Black ABS Plastic
Shock absorber: Integrated into the housing
Carabiner: Twist lock carabiner, silver color, connected to swivel eye
Cable: Galvanized steel wire rope
Fall indicator: Integrated in the hook's swivel
Bottom hook: Double action hook, silver color

... *Read more*

Features: Integrated shock absorber, fall Indicator, RFID
Material: Black ABS plastic, steel
Marking: According to standard, CE-mark
Temperature range: -40°C up to +50°C
Standard: EN 360

Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Fall Arrest Block with Steel Cable POWERTEX FBC

Technical data

Part code	Length m	Max. rated load kg	Hook opening mm	Weight kg
822100600770	6	136	26	2.7
822100900770	9	136	26	3.4
822101200770	12	136	26	5.1
822101800770	18	136	26	6.3

Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved