

Pillar Jib Crane Underbraced 360° PRT

Product information



Appropriate for an indoor or outdoor use, the beam of the PRT is built on an I beam profile designed for an intensive use. The total rotation is on 360° and can be assisted by an engine (optional). The optional installation of a hoist motor direction is possible.

Floor fixing is effected by chemical anchors or anchor rods with foundation.

This model has a wide range of mechanical and electrical options.

Options

- Installation template + anchor rods (or base plate for chemical anchors, keeping its limitations in mind)
- Motorization on main roller (indoor use)
- Top-mounted motorization (outdoor use)
- Hoist power supply cable
- Lockable main switch
- 4-ring electrical collector, for unlimited rotation
- Hot dip galvanizing (contact us)
- Rotation stops to weld onto the assembly
- Single- or multipositions rotation lock
- Outdoor use
- Electric or manual hoist

Part code	WLL ton	Length m	Cap. kg	Delivery time
6025	0.15	2	150	20
6025	0.25	2	250	20
6025	0.5	2	500	20
6025	1	2	1,000	20
6025	1.6	2	1,600	20
6025	2	2	2,000	20
6025	2.5	2	2,500	20
6025	3.2	2	3,200	20
6025	4	2	4,000	20
6025	5	2	5,000	20
6025	6.3	2	6,300	20
6025	8	2	8,000	20
6025	10	2	10,000	20