

## Spur Gear Hand Winch TL150 Painted



### Product information

This small compact hand-operated winch weighing only 4 kg excels because of its high speed. Its speed and size make it well suited to smaller jobs.

- robust and safe winch suitable for lifting and pulling
- Load pressure brake with double ratchet system for safe stable hold of the load in any position
- wire rope outlet upwards
- adjustable crank
- suitable for wall mounting
- 1 layer of paint

### Options:

- zinc-plated finish 6 - 8 micron (EV)
- 2 layers of paint (2L)
- ATEX certified zone 2 and 22 (EX)
- CE II 3G Ex IIC T4 Gc, -20°C<T amb <+70°C
- CE II 3D Ex IIIC T135°C Dc, -20°C<T amb <+70°C

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -20°C up to +70°C

**Finish:** Painted, grey

**Standard:** EN 13157

**Note:** The cable must be ordered separately, ask for more information about our sales

**Safety factor:** 4:1

Part code	Code	WLL ton	Rope Ø mm	Rope capacity m	Capacity 1st layer kg	Capacity top layer kg	Weight kg	Delivery time
501300020000550	TL150	0.15	4	13.1	150	67	4	20

## Blueprint

