



Spur Gear Hand Winch TL300-600 Painted

Product information

This convenient spur gear winch excels by its speed. It is equipped with a load-pressure brake with a double ratchet system and a semi-closed housing. In short, a fine, easy winch!

- robust and safe lifting and pulling winch
- load pressure brake with double ratchet system for safe stable hold of the load in any position
- cable outlet upwards
- adjustable crank
- suitable for wall mounting
- 1 layer of paint

Options:

- zinc-plated finish 6 - 8 micron (EV)
- 2 layers of paint (2L)
- ATEX certified zone 2 and 22 (EX)
CE II 3G Ex IIC T4 Gc, -20°C<T amb <+70°C
CE II 3D Ex IIIC T135°C Dc, -20°C<T amb <+70°C

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -20°C up to +70°C

Finish: Painted, grey

Standard: EN 13157

Note: The cable must be ordered separately, ask for more information about our sales

Safety factor: 4:1

| Part code | Code | WLL ton | Rope Ø mm | Rope capacity m | Capacity 1st layer kg | Capacity top layer kg | Weight kg | Delivery time |
|-----------------|-------|---------|-----------|-----------------|-----------------------|-----------------------|-----------|---------------|
| 501300030000560 | TL300 | 0.3 | 4 | 35.4 | 300 | 172 | 10 | 20 |
| 501300060000560 | TL600 | 0.6 | 6 | 12.3 | 600 | 336 | 11 | 20 |

Blueprint

