Lifting Solutions Group
Axel Johnson International

Screw Clamp TBS for Holland Profile

Product information



Multi-purpose screw clamp for HP-profiles. For use as a (temporary) lifting point in spaces with HP- (bulb) profiles, like sectional ship parts and ship engine rooms. The moment a load is applied, the clamp is automatically fixed.

Features:

- Equipped with a thread spindle for easy attachment, providing a powerful clamping force on the workpiece
- Lightweight design for easy handling
- Tough quality heavy duty body
- Maintenance-friendly, easy to exchange parts which are available upon request

... *Read more*

Marking: CE-mark
Temperature range: - 40°C to +100°C
Warning: Used for HP-100 to HP-240 (bulb) profiles.


Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Screw Clamp TBS for Holland Profile

Blueprint



Technical data

Part code	Code	WLL ton	Jaw width mm	H mm	S mm	T mm	U mm	V mm	X mm	Y mm	Weight kg
502100152401390	1.5 TBS	1.5	100-240	75	74	45	180	150	40	16	2.9
502100302401390	3 TBS	3	100-240	75	75	65	205	150	80	16	6

Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved