

Electric-hydraulic lifting tables 400V

Product information



For installation, repairs, packaging etc. Operating voltage 3-phase /380-400 V/50 Hz. Control device (cable) with lifting and lowering functions, as well as emergency stop. Equipped with a protection frame, which prevents the table from lowering, if something gets in between the plates. Electromagnetic valve, the table can not be lowered (it will stop), if a hose breaks. Delivered completely assembled without plug.

Features: Lifting times 1/2t: 20 sek | 4t: 40 sek

Material: Steel

Marking: According to standard, CE-marked

Finish: Painted, yellow

Standard: EN 1570

Part code	Max load kg	Max height mm	L mm	B mm	L1 mm	B1 mm	H mm	Weight kg	Delivery time
9021NOSP1000H	1,000	990	1,300	820	1,266	680	205 - 990	164	7
9021NOSP2000H	2,000	1,000	1,600	1,000	1,255	785	230 - 1000	270	7
9021NOSP4000H	4,000	1,050	2,000	1,200	1,600	930	240 - 1050	446	7

Technical data

SPARE PARTS

Spare part (product code)

Description

Suitable for lift table (product code/-s)

NOSPHKAPULA

Hand control switch | Incl. cable and plug

NOSP1000H, NOSP2000H, NOSP4000H

NOSPBOX2


Electric control box/unit | New type, with steel connectors

NOSP1000H, NOSP2000H, NOSP4000H

Note: Suitable for lifting tables manufactured after (year) 2013

Also other spare parts available with a delivery time, ask our sales for more information

DIMENSIONS



Model	bottom plate, floor mounting holes (yellow) h3*w3	top plate, lifting eye holes (red) h2*w1-2	diameter of holes for floor fixing	the diameter lift
NOSP1000H	1206*480 mm	1205*410 mm	16 mm	
NOSP2000H	1195*545 mm	the fixed head of a scissor w1: 1130*740 mm roller head of a scissor w2: 1130*440 mm	16 mm	
NOSP4000H	1500*630 mm	1500*540 mm	16 mm	

Blueprint

