Lifting Solutions Group
Axel Johnson International

# Levelling Tool Ganterud

**Product information**



This electric levelling tool levels and handles loads efficiently and safely. Due to its high degree of precision, the work becomes more efficient. This reduces both expensive crane time and waiting times. The levelling tool is operated with a user-friendly, IP67-rated remote control.

The Pro models do also offer auto levelling functionality with released chain wheel which makes it easy to find the centre of gravity of the lifted object. Snatch block function with released chain wheel makes rotation of items easy, quick, and safe.

**Environmental requirements:**

- Storage temperature: -20°C up to +45°C
- Relative humidity (RH): 0 – 90% when stored
- IP rating: IP65

**Handheld controller:**

- Number of function keys: 5/7 for Pro models
- Power output: 10 mW
- Power supply: 3X1,5V AAA
- IP rating: IP67

**Optional equipment:**

- Protective cover
- Extended chain
- Extra batteries
- Transport packaging

... *Read more*

**Marking:** According to standard, CE-mark
**Temperature range:** -20°C up to +40°C
**Standard:** EN 13155

**Certex Lietuva UAB**
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Levelling Tool Ganterud

## Technical data

| Part code | Code | WLL ton | Width mm | Height mm | Chain size mm | Chain length m | Depth mm | Load imbalance capacity max. kg | Reversible stroke pr. hook m | Max. leveling length m | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 6205L3 | L3 | 3 | 503 | 639 | 30.5x10 | 3 | 495 | 500 | 1.5 | 3 (1,5 + 1,5) | 126 |
| 6205L5PRO | L5 PRO | 5 | 503 | 639 | 30.5x10 | 3 | 495 | 750 | 1.5 | 3 (1,5 + 1,5) | 139 |
| 6205L10HeavyDuty | L10 Heavy Duty | 10 | 570 | 720 | 48x16 | 3 | 495 | 4,000 | 1.5 | 3 (1,5 + 1,5) | 180 |
| 6205L12PRO | L12 PRO | 12 | 740 | 750 | 48x16 | 4 | 595 | 2,500 | 2 | 4 (2+2) | 295 |
| 6205L203PRO | L20-3 PRO | 20 | 712 | 1,050 | 60.5x20 | 6 | 623 | 3,000 | 3 | 6 (3+3) | 395 |

**Certex Lietuva UAB**
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved