



Levelling Tool Ganterud

Product information

This electric levelling tool levels and handles loads efficiently and safely. Due to its high degree of precision, the work becomes more efficient. This reduces both expensive crane time and waiting times. The levelling tool is operated with a user-friendly, IP67-rated remote control.

The Pro models do also offer auto levelling functionality with released chain wheel which makes it easy to find the centre of gravity of the lifted object. Snatch block function with released chain wheel makes rotation of items easy, quick, and safe.

Environmental requirements:

- Storage temperature: -20°C up to +45°C
- Relative humidity (RH): 0 – 90% when stored
- IP rating: IP65

Handheld controller:

- Number of function keys: 5/7 for Pro models
- Power output: 10 mW
- Power supply: 3X1,5V AAA
- IP rating: IP67

Optional equipment:

- Protective cover
- Extended chain
- Extra batteries
- Transport packaging

Marking: According to standard, CE-marked

Temperature range: -20°C up to +40°C

Standard: EN 13155

Part code	Code	WLL ton	Width mm	Height mm	Chain length m	Chain diam. mm	Depth mm	Load imbalance capacity max. kg	Reversible stroke pr. hook m	Max. leveling length m	Weight kg	Delivery time
6205L3	L3	3	503	639	3	30,5x10	495	500	1.5	3 (1,5 + 1,5)	126	20
6205L5	L5	5	503	639	3	30,5x10	495	750	1.5	3 (1,5 + 1,5)	139	20
6205L5PRO	L5 PRO	5	503	639	3	30,5x10	495	750	1.5	3 (1,5 + 1,5)	139	2
6205L10HeavyDuty	L10 Heavy Duty	10		-	3	-	-	4,000	1.5	3 (1,5 + 1,5)	180	20
6205L12PRO	L12 PRO	12	740	750	4	48x16	595	2,500	2	4 (2+2)	295	20
6205L203PRO	L20-3 PRO	20	712	1,050	6	60,5x20	623	3,000	3	6 (3+3)	395	20