

Wire Rope Lifting Sling WLS-101

Product information



Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm²*

(*ø 3mm - ø 7mm rope construction: 6x19M WSC 1960 N/mm²)

Design: Both ends mechanically spliced soft eyes

Load table at Technical Data -> [Show table](#)

Please specify the needed (working) length and eye diam/length with your request.

Other rope construction and/or end-terminations such as master links, shackles, hooks, etc.. possible on request. In that case, please check our website for more standard wire rope slings. You can also contact us to discuss the possible options or specify it with your request.

... [Read more](#)

Wire Rope Lifting Sling WLS-101

Technical data

| Part code | Diameter mm | WLL ton |
|-----------|-------------|---------|
| 1603 | 3 | 0.12 |
| 1603 | 4 | 0.21 |
| 1603 | 5 | 0.32 |
| 1603 | 6 | 0.47 |
| 1603 | 8 | 0.82 |
| 1603 | 9 | 1.04 |
| 1603 | 10 | 1.28 |
| 1603 | 11 | 1.55 |
| 1603 | 12 | 1.84 |
| 1603 | 13 | 2.17 |
| 1603 | 14 | 2.51 |
| 1603 | 16 | 3.3 |
| 1603 | 18 | 4.1 |
| 1603 | 20 | 5.1 |
| 1603 | 22 | 6.2 |
| 1603 | 24 | 7.38 |
| 1603 | 26 | 8.66 |
| 1603 | 28 | 10.04 |
| 1603 | 32 | 13.12 |
| 1603 | 36 | 16.59 |
| 1603 | 40 | 20.56 |
| 1603 | 44 | 24.78 |
| 1603 | 48 | 29.55 |
| 1603 | 52 | 34.69 |