Lifting Solutions Group
Axel Johnson International

Wire Rope Lifting Sling WLS-175

Product information



Standard steel wire rope construction: 6x36WS IWRC, 1960N/mm2*
(*ø 3mm - ø 7mm rope constrcution: 6x19M WSC 1960 N/mm2)
Design: Master link in one end and eyehook with safety latch in other end, mechanical aluminium spliced.

Load table at Technical Data -> Show table

Please specify the needed (working) length with your request.

Other rope construction and/or end-terminations such as master links, shackles, hooks, etc.. possible on request. In that case, please check our website for more standard wire rope slings. You can also contact us to discuss the possible options or specify it with your request.

... *Read more*

Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Wire Rope Lifting Sling WLS-175

Technical data

Part code	Diameter mm	WLL ton
1603	3	0.12
1603	4	0.21
1603	5	0.32
1603	6	0.47
1603	7	0.64
1603	8	0.82
1603	10	1.28
1603	12	1.84
1603	14	2.51
1603	16	3.3
1603	18	4.1
1603	20	5.1
1603	22	6.2
1603	24	7.38
1603	26	8.66
1603	28	10.04
1603	32	13.12
1603	36	16.59
1603	40	20.56
1603	44	24.78
1603	48	29.55
1603	52	34.69

Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved