

Certex Chain Slings CS-165 Grade 80



Product information



Assembled 1-Leg chain sling with latch hook and grab hook. Slings are equipped with a load plate.

Sling length measured from the top of the master link to the bottom of the hook.

Material: Alloy Steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C / 400°C = WLL 75%

Finish: Painted, black / yellow

Standard: EN 818-4

Note: The last three digits of the product code refer to the length: 010 = 1,0 m.

Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

| Part code | WLL ton |
|-----------------|---------|
| 230500600100010 | 1.12 |
| 230500600150010 | 1.12 |
| 230500600200010 | 1.12 |
| 230500600250010 | 1.12 |
| 230500600000010 | 1.12 |
| 230500800100010 | 2 |
| 230500800150010 | 2 |

| | |
|-----------------|------|
| 230500800200010 | 2 |
| 230500800000010 | 2 |
| 230501000150010 | 3.15 |
| 230501000200010 | 3.15 |
| 230501000250010 | 3.15 |
| 230501000300010 | 3.15 |
| 230501000000010 | 3.15 |
| 230501300200010 | 5.3 |
| 230501300250010 | 5.3 |
| 230501300300010 | 5.3 |
| 230501300350010 | 5.3 |
| 230501300000010 | 5.3 |
| 230501600200010 | 8 |
| 230501600250010 | 8 |
| 230501600300010 | 8 |
| 230501600350010 | 8 |
| 230501600000010 | 8 |
| 230502000300010 | 12.5 |
| 230502000400010 | 12.5 |
| 230502000000010 | 12.5 |