



Wire rope pullers

Product information



RVT1500S

High-quality puller for professional use with a direction changer and an automatic friction brake working in both directions. Convertible configuration between 1- and 2-line system. The pulling capacity is 0.75 t and the total length is about 2.7 m when the cable is simple. If the cable is attached to the frame with a hook, i.e. doubled, the pulling capacity is then 1.5 t and the total length is about 1.6 m. The handle can be rotated 360 degrees.

RVT900

A light but strong puller with a fixed 2-line system with a draw capacity of 2 t. The operation is based on a mechanical ratchet lever brake without a reversing function.

RVT2000

A sturdy puller with a convertible configuration between a 1- and 2-line system. The pulling capacity is 2 t and the length is about 3 m when the cable is simple. If the cable is attached to the frame with a hook, i.e. doubled, the pulling capacity is then 4 t and the length is about 1.5 m. The operation is based on a mechanical ratchet lever brake without a reversing function.

Material: Steel

Note: Not to be used as a lifting device

Part code	Rope length m	Working length m	Pulling capacity t	Wire Ø mm	Min height mm	Weight kg	Delivery time
494500200010	1.4	1,8	2	4.8	550	3.5	5
494500200010	3,0 / 1,5	3,5 / 2,05	2 / 4	5	650	4.5	7
494500750010	2,4 / 1,2	2,7 / 1,6	0,75 / 1,5	6	-	4.6	5