



Steel Wire Rope 6x24-7FC

Product information



Rope construction: 6x24-7FC.

Marking: According to standard

Standard: EN 12385-4

Fill factor: 0.41

Slings



| Part code | Rope diameter mm | Tensile strength N/mm ² | Finish | Rope lay | Min. breaking force kN | Steel area mm ² | Lubrication | Weight kg/100m | Delivery time |
|-----------------|---------------------|---------------------------------------|------------|----------|---------------------------|-------------------------------|-------------|-------------------|---------------|
| 101100604250310 | 6 | 1,770 | Galvanized | sZ | 17.9 | 11.6 | Dry | 11 | 7 |
| 101100804250310 | 8 | 1,770 | Galvanized | sZ | 31.8 | 20.6 | Dry | 20 | 7 |
| 101101004250310 | 10 | 1,770 | Galvanized | sZ | 49.6 | 32.2 | Dry | 32 | 7 |
| 101101204250310 | 12 | 1,770 | Galvanized | sZ | 71.4 | 46.4 | Dry | 46 | 7 |
| 101101404250310 | 14 | 1,770 | Galvanized | sZ | 97.2 | 63.1 | Dry | 62 | 20 |
| 101101604250310 | 16 | 1,770 | Galvanized | sZ | 127 | 82.4 | Dry | 81 | 20 |
| 101101804250310 | 18 | 1,770 | Galvanized | sZ | 161 | 104 | Dry | 103 | 7 |
| 101102004250310 | 20 | 1,770 | Galvanized | sZ | 198 | 129 | Dry | 127 | 20 |
| 101102204250310 | 22 | 1,770 | Galvanized | sZ | 240 | 156 | Dry | 154 | 7 |