

Modular Lifting Beam PALEM

Product information



PALEM modular spreader bar.

- Beam composed of 2 end pieces with shackles + intermediate spacers.
- Supplied with top and bottom shackles + connecting bolts.
- Supplied without upper and lower slings.
- Lifting capacities can be adjusted according to the length and head angle of the slings (see tables).
- Protection: grinding SA 2.5 + polyester powder painting 60 microns C2.
- RAL 1028 yellow finish.
- Delivered with user's and maintenance manual and CE certificate of compliance.
- For higher capacities or other models, please contact us.
- Packing under shrink film for transport by truck.

Material: Steel

Marking: According to standard, CE-marked

Finish: SA 2.5 + polyester powder painting 60 microns C2

Standard: EN 13155

Note: Not suitable for sea freight

Part code	WLL ton	Length mm	Delivery time
6205EXT06250	6	2x250	20
6205EN06100	6	100	20
6205EN06200	6	200	20
6205EN06300	6	300	20
6205EN06500	6	500	20

6205EN061000	6	1,000	20
6205EN061500	6	1,500	20
6205EXT12250	12	2x250	20
6205EN12500	12	500	20
6205EN121000	12	1,000	20
6205EN122000	12	2,000	20
6205EXT24500	24	2x500	20
6205EN24500	24	500	20
6205EN241000	24	1,000	20
6205EN242000	24	2,000	20
6205EXT34500	34	2x500	20
6205EN34500	34	500	20
6205EN341000	34	1,000	20
6205EN342000	34	2,000	20
6205EN344000	34	4,000	20
6205EXT50500	50	2x500	20
6205EN50500	50	500	20
6205EN501000	50	1,000	20
6205EN502000	50	2,000	20
6205EN504000	50	4,000	20
6205EXT70500	70	2x500	20
6205EN70500	70	500	20
6205EN701000	70	1,000	20

6205EN702000	70	2,000	20
6205EN704000	70	4,000	20