



Stay rope



Agriculture and livestock



## Steel Wire Rope Ropetex S19 Stainless Steel

### Product information

**ROPETEX**



ROPETEX S19 is a stainless steel wire rope. It's very corrosion resistant and durable, well suited for marine applications. The S19 rope has very little stretch which makes it excellent for standing rigging, stays, controls and architectural balustrades and green walls.

ROPETEX S19 can be provided with swaged terminals as end fittings.

**Rope construction:** 1x19

**Material:** AISI 316 / EN 1.4401

**Marking:** According to standard

**Temperature range:** -40°C up to +200°C

**Standard:** EN 12385-10

*except material*

**Warning:** Not to be used for lifting purposes

**Fill factor:** 0,74

Part code	Rope diameter mm	Tensile strength N/mm <sup>2</sup>	Finish	Rope lay	Min. breaking force kN	Steel area mm <sup>2</sup>	Lubrication	Weight kg/100m	Delivery time
108100101620018	1	1,570	Stainless	S	0.83	0.58	No-Lube	0.49	20
108100131620018	1.25	1,570	Stainless	S	1.29	0.91	No-Lube	0.74	20
108100151620018	1.5	1,570	Stainless	S	1.86	1.31	No-Lube	1.09	20
108100201620018	2	1,570	Stainless	S	3.3	2.33	No-Lube	1.94	20
108100251620018	2.5	1,570	Stainless	S	5.16	3.65	No-Lube	3.03	20
108100301620018	3	1,570	Stainless	S	7.43	5.25	No-Lube	4.37	20
108100401620018	4	1,570	Stainless	S	13.2	9.34	No-Lube	7.76	20
108100501620018	5	1,570	Stainless	S	20.6	14.6	No-Lube	12.1	20
108100601620018	6	1,570	Stainless	S	29.7	21	No-Lube	17.5	20
108100701620018	7	1,570	Stainless	S	40.5	28.6	No-Lube	23.8	20
108100801620018	8	1,570	Stainless	S	52.8	37.4	No-Lube	31	20
108101001620018	10	1,570	Stainless	S	82.6	58.4	No-Lube	48.5	20