

## Turnbuckle US.std

### Product information



Forged according to U.S. specification FF-T-791. Dimension 3/8" up to and including 5/8" are provided with screw and nut in the jaw, other dimension with pin and cotter pin.

**Material:** Alloy steel.

**Finish:** Galvanized.

**Note:** The turnbuckles are offered in three different designs, jaw-jaw, jaw-eye and eye-eye.

**Safety factor:** 5:1

Part code	WLL ton	Take up mm	Thread inch	A,	B,	C,	d mm	E,	F,	H,	L	S mm	Weight kg	Delivery time
422100230050	0.23	100	1/4	23	11	16	6.4	8.6	45	19	205	6	0.14	17
422100360050	0.36	115	5/16	25	12	22	6.4	11	53	23	242	7	0.23	17
422100540050	0.54	150	3/8	29	13	22	8	13	65	28	302	9	0.34	17
422100100050	1	150	1/2	36	16	26	9.5	18	80	36	338	12	0.69	17
422100100055	1	230	1/2	36	16	26	9.5	18	80	36	414	12	0.78	17
422100100056	1	300	1/2	36	16	26	9.5	18	80	36	490	12	0.93	17
422100160050	1.59	150	5/8	44	18	33	13	21	98	43	394	14	1.1	17
422100160055	1.59	230	5/8	44	18	33	13	21	98	43	470	14	1.4	17

422100160056	1.59	300	5/8	44	18	33	13	21	98	43	546	14	1.7	17
422100240050	2.36	150	3/4	55	23	38	15.5	25	113	53	432	17	1.8	17
422100240055	2.36	230	3/4	55	23	38	15.5	25	113	53	508	17	2	17
422100240056	2.36	300	3/4	55	23	38	15.5	25	113	53	584	17	2.4	17
422100240057	2.36	460	3/4	55	23	38	15.5	25	113	53	737	17	3	17
422100330050	3.27	300	7/8	63	27	44	19	31	118	59	625	20	3.5	17
422100330055	3.27	778	7/8	63	27	44	19	31	118	59	778	20	4.2	17
422100450055	4.54	150	1	70	30	52	22	36	155	74	524	22	4.1	17
422100450057	4.54	300	1	70	30	52	22	36	155	74	676	22	5.1	17
422100450056	4.54	460	1	70	30	52	22	36	155	74	829	22	6	17
422100450050	4.54	610	1	70	30	52	22	36	155	74	980	22	7.4	17
422100690050	6.9	300	1 1/4	94	44	73	29	45	197	88	760	29	8.8	17
422100690055	6.9	460	1 1/4	94	44	73	29	45	197	88	912	29	11	17
422100690056	6.9	610	1 1/4	94	44	73	29	45	197	88	1,064	29	13	17
422100970050	9.71	300	1 1/2	106	52	70	35	54	215	105	823	32	13	17
422100970055	9.71	460	1 1/2	106	52	70	35	54	215	105	975	32	15	17
422100970056	9.71	610	1 1/2	106	52	70	35	54	215	105	1,128	32	18	17
422101270050	12.7	460	1 3/4	125	59	85	41	60	254	119	1,060	38	22	17
422101270055	12.7	610	1 3/4	125	59	85	41	60	254	119	1,213	38	28	17
422101680050	16.78	610	2	142	64	93	51	69	308	146	1,315	45	43	17
422102720050	27.22	610	2 1/2	151	75	114	57	79	344	165	1,486	51	68	17
422103400050	34.02	610	2 3/4	173	89	110	70	83	381	178	1,562	57	91	17

## Blueprint

