Lifting Solutions Group
Axel Johnson International

Safety Tripod TM9-N

Product information



Lightweight aluminum safety tripod for use in manholes, shafts, evacuation, lifting and as a component of fall protection equipment. It provides protection for up to 3 people simultaneously.

Since the winch is installed on the outside of the leg, this tripod provides good workspace inside the tripod.
The steel head is equipped with 3 ball-bearing polyamide rollers for guidance of the work rope of evacuation devices, and 3 anchor points for fall protection equipment.

- Anchor points on head: 3
- Leg spacing: 2 m
- Shipping dimensions: 1.75 x 0.25 x 0.25 m

Diameter of the opening below the tripod: 109-150 cm
Feet spacing: 0.93-1.28 cm

... *Read more*

Material: Aluminium, galvanized powder-coated steel, polyamid and composite
Marking: According to standard, According to standard
Standard: EN 795B, CEN/TS/16415
Note: Winch and block should be ordered separately. One anchor point can only be used by 1 user at a time.

Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Safety Tripod TM9-N

Technical data

Part code	Diameter mm	WLL ton	Max. number of persons	Height m	Weight kg
825200150070	109	0.5	3	2.09	15.45

Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved