
Lifting Solutions Group
Axel Johnson International

T-Bar for Single-blade Lifting

Product information



Universal spreader beam for operation and maintenance, as well as wind turbine blade replacement. The kit consists of a 3-leg adjustable chain sling, two webbing slings of different lengths, and two round slings.

The blade surfboard features adjustable pads that protect the blades from pressure and damage. The beam has integrated lifting points for easy attachment of lifting slings.

Operation:

- Single crane lift
- Low clearance under blade
- Manual (CoG) compensation on the ground
- Load distributing blade board system
- Simple adjustable chain rig for different blade sizes

Assembly time with 2 technicians + a crane: 1 hour.

... *Read more*

Marking: According to standard
Temperature range: -20°C up to +50°C
Standard: EN 13155
Note: User manual and 3D available on request

Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

T-Bar for Single-blade Lifting

Technical data

Part code	WLL ton	Dimensions L x W x H mm	Weight kg
6208AXL000001	14	11300 x 2850 x 3100	2,600

Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved