

Pushable electric stacking trucks

Product information



For warehouses and production facilities. Light to push and direct on a smooth surface and fits to operate even in narrow corridors. Turning circle is only 1245 mm. Can be operated also as a moveable and ergonomic working and assembly platform. Battery capacity is 120 Ah and automatic re-charger and indicator for battery charge is included. Equipped with a mechanical brake and nylon wheels. Equipped with nylon wheels.

Height of the stacking truck when the mast is raised to the maximum height:

- PINK100030: 3560 mm
- PINK150035: 4060 mm

... [Read more](#)

Marking: CE-marked

Note: Load center distance 500 mm

Pushable electric stacking trucks

Technical data

Part code	WLL ton	Lifting height m	Length mm	Height mm	Width mm	Width of forks mm	Length of forks mm	Operation voltage (V)	Weight kg
5498PINK100030	1	3	1,750	2,090	800	570	1,150	12	429
5498PINK150035	1.5	3.5	1,840	2,340	800	570	1,150	24	563

SPARE PARTS

Spare part (product code)	Description	Suitable for stacker (product code)
PINKETUPYORA	Front/fork wheel Incl. bearings & accessories	PINK100030, PINK150035
PINKISOPYORA	Turning (big) wheel Incl. bearings	PINK100030, PINK150035
PINKSULAKE	Fuse assembly, complete	PINK100030, PINK150035
PINKOHJAUSKETJU	Steering chain Complete assembly Incl. 2 chain halves and 2 connectors	PINK100030, PINK150035
PINKVO15	Electric door lock Incl. keys	PINK100030, PINK150035
PINKVO16	Torsional spring for handle Upright spiral model	PINK100030, PINK150035
PINK100030KAJ	Handle spring Horizontal spiral model	PINK100030 (older model)
PINK100030LATURI	Charger	PINK100030
PINK150035LATURI	Charger	PINK150035
PINK100030AKKU	Battery 12 V	PINK100030 (1 pc), PINK150035 (2 pcs)
PINK100030CO	Coulombmeter / Power indicator	PINK100030
PINK150035CO	Coulombmeter / Power indicator	PINK150035

Also other spare parts available with a delivery time, ask our sales for more information