

Electric Chain Hoist LIFTKET STAR ONE 030 125 - 1.000 kg

Product information



Electric Chain Hoist Liftket STAR ONE impresses with its load-dependent speed control. Thanks to its speed ramp, it enables smooth acceleration and deceleration. STAR ONE can be easily connected to any single-phase grid with a voltage of 110 to 240 V and a frequency of 50 or 60 Hz. This wide compatibility enables universal use worldwide, regardless of regional power grid standards. This makes the device ideal for international applications and various locations.

Features:


- Single-phase grid
- Load-dependent lifting speeds
- Power supply 230 V, 1 phase, 50 Hz
- Up to 1.000 kg load capacity
- Standard lifting height 3 m
- 1.5m control cable
- Control pendant with emergency stop
- Protection class IP55
- Equipped with EASY CONNECT
- VFD control 24 V DC
- Upper/lower limit switches
- Starting and slowing down by speed ramp

... [Read more](#)

Marking: CE-marked

Electric Chain Hoist LIFTKET STAR ONE 030 125 - 1.000 kg

Blueprint



Technical data

Part code	Code	WLL ton	Lifting height m	Lifting speed m/min	Number of falls	Motor kW	Class ISO/FEM	Load chain mm	A mm	B mm	C mm	G mm	H mm	I mm	J mm	K mm	M mm	N mm	O mm	P mm	V mm	Weight kg
540100011470794	125/1-8	0.125	3	8	1	0.70/0.00	M4/ 1Am	5.2x15	221	235	220	365	525	15	20	19	12	37	40	24	74	22
540100031410794	250/1-8	0.25	3	7	1	0.70/0.00	M4/ 1Am	5.2x15	221	235	220	365	525	15	20	19	12	37	40	24	74	22
540100051290794	500/1-8	0.5	3	5	1	0.70/0.00	M4/ 1Am	5.2x15	221	235	220	365	525	15	20	19	12	37	40	24	74	22
540100102140794	1000/2-4	1	3	2,5	2	0.70/0.00	M4/ 1Am	5.2x15	221	235	220	428	540	19	22	24	12	37	40	24	74	26