



Electric Chain Hoist LIFTKET STAR ONE 030 125 - 1.000 kg

Product information

Electric Chain Hoist Liftket STAR ONE impresses with its load-dependent speed control. Thanks to its speed ramp, it enables smooth acceleration and deceleration. STAR ONE can be easily connected to any single-phase grid with a voltage of 110 to 240 V and a frequency of 50 or 60 Hz. This wide compatibility enables universal use worldwide, regardless of regional power grid standards. This makes the device ideal for international applications and various locations.

Features:

- Single-phase grid
- Load-dependent lifting speeds
- Power supply 230 V, 1 phase, 50 Hz
- Up to 1.000 kg load capacity
- Standard lifting height 3 m
- 1.5m control cable
- Control pendant with emergency stop
- Protection class IP55
- Equipped with EASY CONNECT
- VFD control 24 V DC
- Upper/lower limit switches
- Starting and slowing down by speed ramp

Marking: CE-marked

| Part code | Code | WLL ton | Lifting height m | Lifting speed m/min | Number of falls | Motor kW | Class ISO/FEM | Load chain mm | A, B, C, G, H, I | J, K, M | N | O | P | V | Weight kg | Delivery time | | |
|-----------------|----------|---------|------------------|---------------------|-----------------|-----------|---------------|---------------|---------------------|---------|-------|----|----|----|-----------|---------------|----|----|
| 540100011470794 | 125/1-8 | 0.125 | 3 | 8 | 1 | 0.70/0.00 | M4/ 1Am | 5.2x15 | 221 235 220 365 525 | 15 | 20 19 | 12 | 37 | 40 | 24 | 74 | 22 | 20 |
| 540100031410794 | 250/1-8 | 0.25 | 3 | 7 | 1 | 0.70/0.00 | M4/ 1Am | 5.2x15 | 221 235 220 365 525 | 15 | 20 19 | 12 | 37 | 40 | 24 | 74 | 22 | 20 |
| 540100051290794 | 500/1-8 | 0.5 | 3 | 5 | 1 | 0.70/0.00 | M4/ 1Am | 5.2x15 | 221 235 220 365 525 | 15 | 20 19 | 12 | 37 | 40 | 24 | 74 | 22 | 20 |
| 540100102140794 | 1000/2-4 | 1 | 3 | 2,5 | 2 | 0.70/0.00 | M4/ 1Am | 5.2x15 | 221 235 220 428 540 | 19 | 22 24 | 12 | 37 | 40 | 24 | 74 | 26 | 20 |

Blueprint

