



Pillar Jib Crane Type SK-I

Product information



We recommend this type of pillar jib crane for lifting and handling of loads heavier than 500 kg. Our standard programme has been designed in load groups from 500 kg up to 3.200 kg. All these jib cranes are designed with an IPE-profile jib arm, which is ideal for use together with an electrical trolley. The cranes are assembled with a separate C-profile for cable, hose etc.

Electrical chainhoist: When using an electrical chain hoist we can offer a wide selection of hoists as well as electrical and manual trolleys. We recommend an electrical trolley for this type of crane.

Design: Lightweight welded beam construction providing good torsional stiffness.

Proof load: Usually 1,5 x WLL.

Material: Beam and plate of high-strength structural steel.

Marking: Working load limit (WLL), CE marking, manufacturer, serial number, year of manufacturing, etc.

Finish: Yellow painted. Other treatments available on request.

Part code	WLL ton	Type	Max. hoist weight kg	IPE	Flange width mm	L mm	L1 mm	H mm	H1 mm	H2 mm	Ø D mm	Weight kg	Delivery time
60255220053000	0.5	SK-I-500/3	55	120	64	3,000	2,500	4,000	750	3,285	580	555	20
60255220054000	0.5	SK-I-500/4	55	140	73	4,000	3,500	4,000	750	3,285	580	555	20
60255220055000	0.5	SK-I-500/5	55	160	82	5,000	4,500	4,000	750	3,285	580	555	20
60255220056000	0.5	SK-I-500/6	55	160	82	6,000	5,500	4,000	750	3,285	680	555	20
60255220103000	1	SK-I-1000/3	58	140	73	3,000	2,500	4,000	750	3,285	580	1,058	20
60255220104000	1	SK-I-1000/4	58	160	82	4,000	3,500	4,000	750	3,285	680	1,058	20
60255220105000	1	SK-I-1000/5	58	180	91	5,000	4,500	4,000	1,000	3,070	680	1,058	20
60255220106000	1	SK-I-1000/6	58	200	100	6,000	5,500	4,000	1,000	3,070	810	1,058	20
60255220203000	2	SK-I-2000/3	88	180	91	3,000	2,500	4,000	1,000	3,070	680	2,088	20
60255220204000	2	SK-I-2000/4	88	200	100	4,000	3,500	4,000	1,000	3,070	810	2,088	20

Blueprint

