Lifting Solutions Group
Axel Johnson International

# Pillar Jib Crane Type SK-IL

## Product information




We recommend this type of pillar jib crane when the lifting height is limited. Our standard programme has been designed in load groups from 125 kg up to 3.200 kg. This type of crane has been designed without counter bracing which maximises the lifting height considerably.
All these cranes have been designed with an IPE-profile jib arm, which is ideal for use together with an electrical trolley.
The jib cranes are assembled with a separate C-profile for cable, hose etc.

**Proof load:** Usually 1,5 x WLL.

... *Read more*

**Material:** Beam and plate of high-strength structural steel.
**Marking:** Working load limit (WLL), CE marking, manufacturer, serial number, year of manufacturing, etc.
**Finish:** Yellow painted. Other treatments available on request.

**Certex Lietuva UAB**
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

# Pillar Jib Crane Type SK-IL

## Technical data

| Part code | WLL ton | Type | Max. hoist weight kg | IPE | Flange width mm | L mm | L1 mm | H mm | H1 mm | H2 mm | Ø D mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 60255230012000 | 0.125 | SK-IL-125/2 | 40 | 120 | 64 | 2,000 | 500 | 4,000 | 750 | 3,820 | 430 | 165 |
| 60255230013000 | 0.125 | SK-IL-125/3 | 40 | 200 | 100 | 3,000 | 500 | 4,000 | 750 | 3,740 | 430 | 165 |
| 60255230014000 | 0.125 | SK-IL-125/4 | 40 | 240 | 120 | 4,000 | 500 | 4,000 | 750 | 3,700 | 430 | 165 |
| 60255230015000 | 0.125 | SK-IL-125/5 | 40 | 300 | 150 | 5,000 | 500 | 4,000 | 750 | 3,640 | 430 | 165 |
| 60255230022000 | 0.25 | SK-IL-250/2 | 45 | 180 | 91 | 2,000 | 500 | 4,000 | 750 | 3,760 | 430 | 295 |
| 60255230023000 | 0.25 | SK-IL-250/3 | 45 | 220 | 110 | 3,000 | 500 | 4,000 | 750 | 3,720 | 430 | 295 |
| 60255230024000 | 0.25 | SK-IL-250/4 | 45 | 300 | 150 | 4,000 | 500 | 4,000 | 750 | 3,670 | 430 | 295 |
| 60255230025000 | 0.25 | SK-IL-250/5 | 45 | 330 | 160 | 5,000 | 500 | 4,000 | 750 | 3,610 | 580 | 295 |
| 60255230052000 | 0.5 | SK-IL-500/2 | 55 | 200 | 100 | 2,000 | 500 | 4,000 | 750 | 3,740 | 430 | 555 |
| 60255230053000 | 0.5 | SK-IL-500/3 | 55 | 270 | 135 | 3,000 | 500 | 4,000 | 750 | 3,670 | 580 | 555 |
| 60255230054000 | 0.5 | SK-IL-500/4 | 55 | 300 | 150 | 4,000 | 500 | 4,000 | 750 | 3,640 | 580 | 555 |
| 60255230055000 | 0.5 | SK-IL-500/5 | 55 | 360 | 170 | 5,000 | 500 | 4,000 | 1,000 | 3,560 | 680 | 555 |
| 60255230102000 | 1 | SK-IL-1000/2 | 58 | 270 | 110 | 2,000 | 500 | 4,000 | 750 | 3,720 | 580 | 1,058 |
| 60255230103000 | 1 | SK-IL-1000/3 | 58 | 400 | 160 | 3,000 | 500 | 4,000 | 750 | 3,610 | 580 | 1,058 |
| 60255230104000 | 1 | SK-IL-1000/4 | 58 | 400 | 180 | 4,000 | 500 | 4,000 | 1,000 | 3,510 | 680 | 1,058 |
| 60255230202000 | 2 | SK-IL-2000/2 | 88 | 270 | 135 | 2,000 | 500 | 4,000 | 750 | 3,650 | 680 | 2,088 |
| 60255230203000 | 2 | SK-IL-2000/3 | 88 | 360 | 170 | 3,000 | 500 | 4,000 | 1,000 | 3,560 | 810 | 2,088 |
| 60255230204000 | 2 | SK-IL-2000/4 | 88 | 450 | 190 | 4,000 | 500 | 4,000 | 1,000 | 3,470 | 810 | 2,088 |

**Certex Lietuva UAB**
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved