

## Chain Sling Powertex 1-leg with Safety Hook, Grade 10

### Product information



The Chain Sling Powertex 1-leg with safety hook is a single-leg lifting assembly for general industrial use. It is designed for controlled vertical lifting where secure attachment, optional shortening, and predictable performance are required.

The standard assembly includes a master link, a Grade 10 chain, a shortening grab hook, a safety hook, and a marking plate with WLL information. This provides a complete and ready-to-use configuration for everyday lifting tasks.

The sling can also be supplied in alternative configurations with different hooks, master links, or shortening options on request.

### When to choose this product

#### Best for:

- Straight vertical lifts with a single lifting point
- Applications where secure hook closure is preferred during lifting

#### Product benefits

- Safety hook provides a more secure connection, helping reduce the chance of unintentional hook release during lifting
- Shortening grab hook allows chain length adjustment, supporting accurate load positioning without extra components
- Grade 10 chain provides higher capacity compared to Grade 8, enabling compact setups without increasing chain diameter
- Components are crack detection tested, and samples from each batch are proof load tested, supporting consistent quality control
- Fatigue rated to 20,000 cycles at 1.5x WLL, helping maintain predictable behaviour in repetitive lifting applications
- Marking plate shows WLL and angle capacities, simplifying load planning and reducing interpretation errors on site [... Read more](#)

**Material:** Alloy steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to +200°C without reduction in WLL

**Finish:** Red powder paint

**Standard:** EN 818-4  
(+25 % WLL)

**Safety factor:** 4:1

**Grade:** 10

## Chain Sling Powertex 1-leg with Safety Hook, Grade 10

### Technical data

Part code	WLL ton
240500600100270	1.4
240500600200270	1.4
240500600300270	1.4
240500600600270	1.4
240500800100270	2.5
240500800200270	2.5
240500800300270	2.5
240500800600270	2.5
240501000100270	4
240501000200270	4
240501000300270	4
240501000600270	4
240501300100270	6.7
240501300200270	6.7
240501300300270	6.7
240501300600270	6.7
240501600300270	10
240501600600270	10
240501600800270	10
240502000400270	16
240502000600270	16
240502000800270	16
240502200400270	19
240502200600270	19
240502200800270	19
240502600600270	26.5
240502600800270	26.5
240503200600270	40
240503200800270	40