



Chain Sling Powertex 2-leg with Latch Hooks, Grade 10

Product information

The Chain Sling Powertex 2-leg with latch hooks is a two-leg lifting assembly for general industrial use. It is designed for balanced lifting where load distribution across two lifting points, fast connection, and predictable performance are required.

The standard assembly includes a master link, Grade 10 chains, shortening grab hooks, latch hooks, and a marking plate with WLL information. This provides a complete and ready-to-use configuration for everyday lifting tasks.

The sling can also be supplied in alternative configurations with different hooks, master links, or shortening options on request.

When to choose this product

Best for:

- Balanced lifting using two lifting points
- Repetitive lifting where quick hook engagement improves efficiency

Product benefits

- Latch hook enables fast and secure attachment, reducing connection time during repetitive lifting operations
- Integrated grab hook allows chain shortening, supporting accurate load positioning without extra components
- Grade 10 chain provides higher capacity compared to Grade 8, enabling compact setups without increasing chain diameter
- Components crack detection tested, and samples are proof load tested.
- Fatigue rated to 20,000 cycles at 1.5x WLL, helping maintain predictable behaviour in repetitive lifting applications
- Marking plate shows WLL and angle capacities, simplifying load planning and reducing interpretation errors on site

Configuration notes

Assemblies up to 22 mm can be equipped with a clevis connection, while all variants can also be built with connecting links. Chain sling assemblies from 26 mm chain are supplied with sling hooks with eye and connecting link, and grab hooks with eye connected with connecting link.

Material: Alloy steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C without reduction in WLL

Finish: Red powder paint

Standard: EN 818-4

(+25 % WLL)

Safety factor: 4:1

Grade: 10

Part code	WLL ton
240800600100200	2
240800600200200	2
240800600300200	2
240800600400200	2
240800600500200	2
240800600600200	2
240800600700200	2
240800600800200	2
240800800100200	3.55
240800800200200	3.55
240800800300200	3.55
240800800400200	3.55
240800800500200	3.55
240800800600200	3.55
240800800700200	3.55
240800800800200	3.55
240801000100200	5.6
240801000200200	5.6
240801000300200	5.6

240801000400200	5.6
240801000500200	5.6
240801000600200	5.6
240801000700200	5.6
240801000800200	5.6
240801300100200	9.5
240801300200200	9.5
240801300300200	9.5
240801300400200	9.5
240801300500200	9.5
240801300600200	9.5
240801300700200	9.5
240801300800200	9.5
240801600200200	14
240801600300200	14
240801600400200	14
240801600500200	14
240801600600200	14
240801600700200	14
240801600800200	14
240802000200200	22.4
240802000300200	22.4
240802000400200	22.4

240802000500200	22.4
240802000600200	22.4
240802000700200	22.4
240802000800200	22.4
240802200200200	26.5
240802200300200	26.5
240802200400200	26.5
240802200500200	26.5
240802200600200	26.5
240802200700200	26.5
240802200800200	26.5
240802600200200	37.5
240802600300200	37.5
240802600400200	37.5
240802600500200	37.5
240802600600200	37.5
240802600700200	37.5
240802600800200	37.5
240803200200200	56
240803200300200	56
240803200400200	56
240803200500200	56
240803200600200	56

240803200700200

56

240803200800200

56