



## Chain Sling Powertex 2-leg with Latch Hooks, Grade 10

### Product information

The Chain Sling Powertex 2-leg with latch hooks is a two-leg lifting assembly for general industrial use. It is designed for balanced lifting where load distribution across two lifting points, fast connection, and predictable performance are required.

The standard assembly includes a master link, Grade 10 chains, shortening grab hooks, latch hooks, and a marking plate with WLL information. This provides a complete and ready-to-use configuration for everyday lifting tasks.

The sling can also be supplied in alternative configurations with different hooks, master links, or shortening options on request.

#### When to choose this product

##### Best for:

- Balanced lifting using two lifting points
- Repetitive lifting where quick hook engagement improves efficiency

##### Product benefits

- Latch hook enables fast and secure attachment, reducing connection time during repetitive lifting operations
- Integrated grab hook allows chain shortening, supporting accurate load positioning without extra components
- Grade 10 chain provides higher capacity compared to Grade 8, enabling compact setups without increasing chain diameter
- Components crack detection tested, and samples are proof load tested.
- Fatigue rated to 20,000 cycles at 1.5x WLL, helping maintain predictable behaviour in repetitive lifting applications
- Marking plate shows WLL and angle capacities, simplifying load planning and reducing interpretation errors on site

##### Configuration notes

Assemblies up to 22 mm can be equipped with a clevis connection, while all variants can also be built with connecting links. Chain sling assemblies from 26 mm chain are supplied with sling hooks with eye and connecting link, and grab hooks with eye connected with connecting link.

**Material:** Alloy steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to +200°C without reduction in WLL

**Finish:** Red powder paint

**Standard:** EN 818-4

(+25 % WLL)

**Safety factor:** 4:1

Grade: 10

Part code	WLL ton
240800600200200	2
240800600400200	2
240800800200200	3.55
240800800400200	3.55
240801000200200	5.6
240801000400200	5.6
240801300400200	9.5
240801300600200	9.5
240801600400200	14
240801600600200	14
240802000400200	22.4
240802000600200	22.4
240802200500200	26.5
240802600500200	37.5
240803200500200	56