

Chain Sling Powertex 4-leg with Safety Hooks, Grade 10

Product information



The Chain Sling Powertex 4-leg with safety hooks is a four-leg lifting assembly for general industrial use. It is designed for multi-point lifting where load distribution, secure attachment, and predictable performance are required.

The standard assembly includes a master link, Grade 10 chain, shortening grab hooks, safety hooks, and a marking plate with WLL information. This provides a complete and ready-to-use configuration for everyday lifting tasks.

The sling can also be supplied in alternative configurations with different hooks, master links, or shortening options on request.

When to choose this product

Best for:

- Lifting loads requiring multiple lifting points for stability
- Applications where secure hook closure is preferred during lifting

Product benefits

- Safety hooks provide a more secure connection, helping reduce the chance of unintentional hook release during lifting
- Shortening grab hooks allows adjustment of individual legs, supporting improved load balance and positioning
- Four-leg configuration supports load distribution across multiple lifting points, helping stabilize complex or uneven loads
- Grade 10 chain provides higher capacity compared to Grade 8, enabling compact setups without increasing chain diameter
- Components are crack detection tested, and samples from each batch are proof load tested, supporting consistent quality control
- Fatigue rated to 20,000 cycles at 1.5x WLL, helping maintain predictable behavior in repetitive lifting applications [... Read more](#)

Material: Alloy steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C without reduction in WLL

Finish: Red powder paint

Standard: EN 818-4
(+25 % WLL)

Safety factor: 4:1

Grade: 10

Chain Sling Powertex 4-leg with Safety Hooks, Grade 10

Technical data

Part code	WLL ton
241300600200230	3
241300600400230	3
241300800200230	5.3
241300800400230	5.3
241301000200230	8.4
241301000400230	8.4
241301300400230	14
241301300600230	14
241301600400230	21.2
241301600600230	21.2
241302000400230	33.6
241302000600230	33.6
241302200500230	40
241302600500230	56
241303200500230	85