



Chain Sling Powertex 4-leg with Safety Hooks, Grade 10

Product information

The Chain Sling Powertex 4-leg with safety hooks is a four-leg lifting assembly for general industrial use. It is designed for multi-point lifting where load distribution, secure attachment, and predictable performance are required.

The standard assembly includes a master link, Grade 10 chains, shortening grab hooks, safety hooks, and a marking plate with WLL information. This provides a complete and ready-to-use configuration for everyday lifting tasks.

The sling can also be supplied in alternative configurations with different hooks, master links, or shortening options on request.

When to choose this product

Best for:

- Lifting loads requiring multiple lifting points for stability
- Applications where secure hook closure is preferred during lifting

Product benefits

- Safety hooks provide a more secure connection, helping reduce the chance of unintentional hook release during lifting
- Shortening grab hooks allows adjustment of individual legs, supporting improved load balance and positioning
- Four-leg configuration supports load distribution across multiple lifting points, helping stabilise complex or uneven loads
- Grade 10 chain provides higher capacity compared to Grade 8, enabling compact setups without increasing chain diameter
- Components are crack detection tested, and samples from each batch are proof load tested, supporting consistent quality control
- Fatigue rated to 20,000 cycles at 1.5x WLL, helping maintain predictable behaviour in repetitive lifting applications
- Marking plate shows WLL and angle capacities, simplifying load planning and reducing interpretation errors on site
- Full traceability through batch marking supports inspection routines and documentation requirements

Configuration notes

Assemblies up to 22 mm can be equipped with clevis connections, while all variants can also be built with connecting links. Chain sling assemblies from 26 mm chain are supplied with hooks with eye and connecting links.

Material: Alloy steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C without reduction in WLL

Finish: Red powder paint

Standard: EN 818-4

(+25 % WLL)

Safety factor: 4:1

Grade: 10

Part code	WLL ton
241300600100230	3
241300600200230	3
241300600300230	3
241300600400230	3
241300600500230	3
241300600600230	3
241300600700230	3
241300600800230	3
241300800100230	5.3
241300800200230	5.3
241300800300230	5.3
241300800400230	5.3
241300800500230	5.3
241300800600230	5.3
241300800700230	5.3
241300800800230	5.3
241301000100230	8.4
241301000200230	8.4
241301000300230	8.4

241301000400230	8.4
241301000500230	8.4
241301000600230	8.4
241301000700230	8.4
241301000800230	8.4
241301300200230	14
241301300300230	14
241301300400230	14
241301300500230	14
241301300600230	14
241301300700230	14
241301300800230	14
241301600200230	21.2
241301600300230	21.2
241301600400230	21.2
241301600500230	21.2
241301600600230	21.2
241301600700230	21.2
241301600800230	21.2
241302000200230	33.6
241302000300230	33.6
241302000400230	33.6

241302000500230	33.6
241302000600230	33.6
241302000700230	33.6
241302000800230	33.6
241302200200230	40
241302200300230	40
241302200400230	40
241302200500230	40
241302200600230	40
241302200700230	40
241302200800230	40
241302600200230	56
241302600300230	56
241302600400230	56
241302600500230	56
241302600600230	56
241302600700230	56
241302600800230	56
241303200200230	85
241303200300230	85
241303200400230	85
241303200500230	85
241303200600230	85

241303200700230

85

241303200800230

85