Lifting Solutions Group
Axel Johnson International

Standard Reeve Crane Blocks 1 Sheave

Product information



General:
- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

Options:
- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:
Inquiries for custom versions are welcome!

... *Read more*


Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Standard Reeve Crane Blocks 1 Sheave

Blueprint



Technical data

Part code	WLL ton	Model	Rope Ø mm	Sheave dia. mm	Hook size	øD1 mm	øD2 mm	B mm	O mm	TA mm	TB mm	TLmm mm	L mm	T mm	øZ mm	Weight kg
6097SRB260141125E	12.5	SRB 260 .14 .1 .12,5 .E	14	300 / 260	5	300	260	548	55	400	185	933	648	28	32	110
6097SRB260161125E	12.5	SRB 260 .16 .1 .12,5 .E	16	300 / 260	5	300	260	548	55	400	185	933	948	28	32	110
6097SRB22514116E	16	SRB 225 .14 .1 .16 .E	14	260 / 255	5	260	225	548	55	345	180	923	938	28	32	100
6097SRB26016116E	16	SRB 260 .16 .1 .16 .E	16	300 / 260	5	300	260	548	55	400	195	933	948	28	32	110
6097SRB28516116E	16	SRB 285 .16 .1 .16 .E	16	320 / 280	6	320	280	608	57	420	165	908	1,033	28	32	160
6097SRB32016116E	16	SRB 320 .16 .1 .16 .E	16	365 / 320	6	365	320	628	59	450	205	951	1,076	28	32	160
6097SRB32019116E	16	SRB 320 .19 .1 .16 .E	19	365 / 320	6	365	320	628	59	450	205	951	1,081	35	37	160
6097SRB35516116EA	16	SRB 355 .16 .1 .16 .E .A	16	410 / 355	6	410	355	668	59	500	195	1,013	1,138	28	32	180
6097SRB35519116E	16	SRB 355 .19 .1 .16 .E	19	410 / 355	6	410	355	668	59	500	195	1,013	1,138	28	32	180
6097SRB35519120E	20	SRB 355 .19 .1 .20 .E	19	410 / 355	8	410	355	713	76	500	225	1,053	1,204	35	37	225
6097SRB40022129E	29	SRB 400 .22 .1 .29 .E	22	460 / 400	8	460	400	743	69	570	240	1,128	1,273	40	43	290
6097SRB45024132EA	32	SRB 450 .24 .1 .32 .E .A	24	515 / 450	10	515	450	833	76	600	350	1,256	1,422	45	52	455

Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved