

Fast Connector Socket FCS

Product information



Forged clevis fittings with Pin and cutterpin for fast connection of steel wire rope.
Connector shall be used with non-rotating or cat 1. rotation resistant wire rope only.
The connector has to be moulded / casted on the steel wire rope with wirelock resin.

[... Read more](#)

Features: Designed for use with mobile cranes.


Material: Quenched and tempered cast steel.

Finish: Blue painted (P) or hot dip galvanized (G).

Warning: Compare the spelter's and the wire rope's minimum breaking load.

Fast Connector Socket FCS

Blueprint



Technical data

Part code	Code	Rope Ø range mm	MBL ton	Finish	A mm	B mm	C mm	Ø H mm	Ø P mm	T mm	W mm	D mm	Ø D mm	Ø J mm	K mm	TB mm mm	TL mm mm	Weight kg
122101300165	FCS 701 P	11-13	20	Painted	62	61	27	15	25	12	25	50	33	49	46	67	150	1.6
122101300162	FCS 701 PG	11-13	20	Galvanized	62	61	27	15	25	12	25	50	33	49	46	67	150	1.6
122101600165	FCS 702 P	13-16	25	Painted	72	78	32	18	30	14	32	58	38	60	59	85	182	2.6
122101600162	FCS 702 PG	13-16	25	Galvanized	72	78	32	18	30	14	32	58	38	60	59	85	182	2.6
122101900165	FCS 703 P	16-19	40	Painted	85	93	40	21	35	16	38	70	45	70	69	95	218	4.5
122101900162	FCS 703 PG	16-19	40	Galvanized	85	93	40	21	35	16	38	70	45	70	69	95	218	4.5
122102200165	FCS 704 P	20-22	55	Painted	102	106	45	24	41	19	44	80	50	82	81	110	253	6.5
122102200162	FCS 704 PG	20-22	55	Galvanized	102	106	45	24	41	19	44	80	50	82	81	110	253	6.5
122102600165	FCS 705 P	23-26	75	Painted	115	123	60	28	51	22	51	104	60	95	90	128	298	11
122102600162	FCS 705 PG	23-26	75	Galvanized	115	123	60	28	51	22	51	104	60	95	90	128	298	11
122102900165	FCS 706 P	27-29	90	Painted	140	152	65	32	57	25	57	114	70	107	116	142	357	16
122102900162	FCS 706 PG	27-29	90	Galvanized	140	152	65	32	57	25	57	114	70	107	116	142	357	16