

Lever Hoist Elephant YII



Product information

YII Series lever hoists are extremely versatile, suitable for lifting and pulling in many applications. A solid and compact design with special rust-resistant coating performs in extreme environments such as the offshore and mining industries. Extremely lightweight [9.5kg (1.6 Tonne)] The gears are completely enclosed and make the hoist highly reliable and durable meaning lower maintenance costs. One-touch change lever further improves work efficiency. Tough black body resists scratches and prevents rust. Waterproof, shock resistant gear and brake cover. The bolted rubber grip ensures safe operation of the lever hoist.

Material: Chain and hook, alloy steel grade 10.

Marking: WLL, code and CE marking.

Finish: Painted.

Safety factor: 5:1

| Part code | Code | WLL ton | Lifting height m | Number of falls | Load chain mm | D mm | E mm | H mm | Weight kg | Delivery time |
|-----------------|---------|---------|------------------|-----------------|---------------|------|------|------|-----------|---------------|
| 500500020100010 | YII-15 | 0.15 | 1 | 1 | 3 | 195 | 13 | 160 | 0.9 | 20 |
| 500500030150010 | YII-25 | 0.25 | 1.5 | 1 | 4 | 235 | 20 | 155 | 2 | 20 |
| 500500050150010 | YII-50 | 0.5 | 1.5 | 1 | 5 | 265 | 23 | 284 | 3.6 | 20 |
| 500500080150010 | YII-80 | 0.8 | 1.5 | 1 | 5,6 | 290 | 25 | 268 | 6.2 | 20 |
| 500500160150010 | YII-160 | 1.6 | 1.5 | 1 | 7,2 | 350 | 29 | 385 | 9.5 | 20 |
| 500500320150010 | YII-320 | 3.2 | 1.5 | 1 | 9,0 | 420 | 36 | 385 | 15.5 | 20 |
| 500500630150010 | YII-640 | 6.3 | 1.5 | 2 | 9,0 | 570 | 45 | 385 | 26.5 | 20 |

Blueprint

