Lifting Solutions Group
Axel Johnson International

Double Swivel Shackle Codipro SS DSS

Product information



The SS.DSS stainless steel lifting ring is a double swivel ring. It is specially designed for simultaneously lifting and rotating loads. Its double swivel action ensures perfect alignment with the sling.

Features:

- Stainless steel ring that provides maximum corrosion resistance.
- Rotatable under load.
- M45 to M56 or UNC thread available on request.

... *Read more*

Material: AISI 316 L
Marking: According to standard, CE-mark
Temperature range: -20°C up to + 200°C
Standard: EN 1677-1
except grade/WLL

Safety factor: 5:1


Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Double Swivel Shackle Codipro SS DSS

Blueprint



Technical data

Part code	WLL ton	Thread	Torque Nm	StandardL1 mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	L1 mm	S mm	Weight kg
4215SSDSSM24	2.7	M 24 (x3)	160	36	61	31	70	98	73	149	30	36	19	5.2
4215SSDSSM30	3.5	M 30 (x3.5)	250	45	61	31	70	98	73	149	30	45	19	5.2
4215SSDSSM33	3.5	M 33 (x3.5)	250	50	61	31	70	98	73	149	30	50	19	5.2
4215SSDSSM36	5	M 36 (x4)	320	54	61	31	70	98	73	149	30	54	19	5.2
4215SSDSSM36x3	5	M 36 (x3)	320	54	61	31	70	98	73	149	30	54	19	5.2
4215SSDSSM39	5	M 39 (x4)	320	54	61	31	70	98	73	149	30	54	19	5.4
4215SSDSSM42	6	M 42 (x4,5)	400	63	61	31	70	98	73	149	30	63	19	5.4
4215SSDSSM42x3	6	M 42 (x3)	400	63	61	31	70	98	73	149	30	63	19	5.4
4215SSDSSM45	6	M 45 (x4.5)	400	63	61	31	70	98	73	149	30	63	19	5.7
4215SSDSSM48	6.4	M 48 (x5)	600	68	79	38	90	123	91	182	41	68	19	11
4215SSDSSM48x3	6.4	M 48 (x3)	600	68	79	38	90	123	91	182	41	68	19	11
4215SSDSSM48x4	6.4	M 48 (x4)	600	68	79	38	90	123	91	182	41	68	19	11
4215SSDSSM52	6.4	M 52 (x5)	600	68	79	38	90	123	91	182	41	68	19	11.2
4215SSDSSM56	8	M 56 (x5.5)	600	78	79	38	90	123	91	182	41	78	19	11.3
4215SSDSSM56x4	8	M 56 (x4)	600	78	79	38	90	123	91	182	41	78	19	11.4

Certex Lietuva UAB
info@certex.lt
+370 5 2300020

© November 2026 - All Rights Reserved