



Nerūdijanti grandinė siurbliams

Produkto informacija

Application for submersible pumps and breathers in the water and waste water area.

Medžiaga: 1.4404 (AISI 316L), 1.4462 (AISI 318LN).

Atsargos koeficientas: 4:1

Klasė: 6

Produkto kodas	RDA t	Masterlink	Chain	Transition link	Shackle jaw space mm	D mm	W mm	T mm	d mm	w mm	t mm	Pristatymo laikas d.d.
229862515	0,32	AWI 6	WOX 4x12-5	-	18	6	60	35	-	-	-	17
229887067	0,4	AWI 8	WOX 4x12	BWI 5	18	8	60	35	5	26	13	17
229887069	0,56	AWI 8	WOX 5x15	BWI 7	25	8	60	35	7	36	16	17
229887071	0,63	AWI 10	WOX 5x15	BWI 7	25	10	80	50	7	36	16	17
229887073	0,85	AWI 10	WOX 6x18	BWI 7	25	10	80	50	7	36	16	17
229887075	1,25	AWI 13	WOX 7x21	BWI 9	25	13	110	60	9	44	20	17
229887077	1,6	AWI 13	WOX 8x24	BWI 10	32	13	110	60	10	44	20	17
229887079	2,5	AWI 16	WOX 10x30	BWI 13	41	16	110	60	13	54	25	17
229887081	3,5	AWI 18	WOX 13X39	BWI 16	56	18	135	75	17	70	34	17
229887082	6,3	AWI 22	WOX 16x48	BWI 20	56	23	160	90	20	85	40	17
229830193	8	AWI 26	WOX 20x60	BWI 22	76	27	180	100	23	115	50	17
229830196	12	AWI 45	WOX 26x78	BWI 32	76	45	340	180	32	150	70	17

Techninis eskizas

