

Greito surinkimo krano blokas, 4 skriemulių

Produkto informacija



General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent block change is required.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- 4 or 8 point hook locking device.
- Fast reeve guide for fast reeving.
- Safety latch with locking pin.
- C3M finish in signal yellow with black striping.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.


Important:

Inquiries for custom versions are welcome!

[... Read more](#)

Greito surinkimo krano blokas, 4 skriemulių

Techninis eskizas



Greito surinkimo krano blokas, 4 skriemulių

Techninė informacija

Produkto kodas	RDA t	Modelis	Lyno Ø mm	Skriemulio Ø (mm)	Hooksize	Ø D1 mm mm	Ø D2 mm mm	B mm	O mm	TA mm	TB mm	TLmm mm	L mm	T mm	Ø Z mm mm	Svoris kg
6097FRB35519450E	50	FRB 355 .19 .4 .50 .E	19	410 / 355	12	410	355	959	84	500	363	1 229	1 347	35	37	500
6097FRB40022463E	63	FRB 400 .22 .4 .63 .E	22	460 / 400	16	460	400	1 038	97	570	350	1 333	1 465	40	43	540
6097FRB35519463E	63	FRB 355 .19 .4 .63 .E	19	410 / 355	16	410	355	1 038	97	500	343	1 308	1 440	35	37	570
6097FRB45022463E	63	FRB 450 .22 .4 .63 .E	22	510 / 450	16	515	450	1 038	97	600	400	1 448	1 580	40	43	750
6097FRB45024463E	63	FRB 450 .24 .4 .63 .E	24	510 / 450	16	515	450	1 038	97	600	400	1 448	1 580	45	52	750
6097FRB45024480E	80	FRB 450 .24 .4 .80 .E	24	510 / 450	20	515	450	1 183	110	600	527	1 568	1 718	45	52	1 000
6097FRB45026480E	80	FRB 450 .26 .4 .80 .E	26	510 / 450	20	515	450	1 183	110	600	527	1 568	1 718	40	52	1 000
6097FRB52824480E	80	FRB 528 .24 .4 .80 .E	24	590 / 528	20	595	528	1 272	110	710	527	1 736	1 886	45	52	1 000
6097FRB52826480E	80	FRB 528 .26 .4 .80 .E	26	590 / 528	20	595	528	1 272	110	710	527	1 736	1 886	45	52	1 000
6097FRB52828480E	80	FRB 528 .28 .4 .80 .E	28	590 / 528	20	595	528	1 273	110	710	472	1 671	1 821	40	59	1 270
6097FRB528264100E	100	FRB 528 .26 .4 .100 .E	26	590 / 528	25	595	528	1 288	132	710	472	1 743	1 913	40	52	1 270
6097FRB528284100E	100	FRB 528 .28 .4 .100 .E	28	590 / 528	25	595	528	1 288	132	710	472	1 753	1 923	40	59	1 270
6097FRB575284125E	125	FRB 575 .28 .4 .125 .E	28	650 / 575	32	650	575	1 413	137	770	442	1 893	2 083	40	59	1 360
6097FRB670284160E	160	FRB 670 .28 .4 .160 .E	28	760 / 670	40	760	670	1 616	167	870	662	2 181	2 393	50	59	3 150
6097FRB670324160E	160	FRB 670 .32 .4 .160 .E	32	760 / 670	40	760	670	1 616	167	870	662	2 181	2 393	60	66	3 150